I'm not robot
reCAPTCHA
Continue

35 hp vanguard oil capacity

Withstands wear and abuse. Improved protection and durability. Fast, reliable and maintenance-free starting. Engine Type V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross HP* (kW) @ 3'600 rpm 35 Engine Displacement (cc) 993 Cylinder Cast Iron Sleeve Number of Cylinders V-Twin Limited Commercial Warranty † 3 Years Briggs & Stratton Commercial Power introduces the Vanguard Oil Guard System for its 810cc EFI V-Twin and BIG BLOCK commercial engines. Oil Guard is a first-of-its-kind solution for the commercial engine market, offering major productivity gains and allowing for 500-hour oil change intervals. Vanguard engineers developed the system in conjunction with Ferris, a Briggs & Stratton brand. The technology first launched on 2017 Ferris mowers, and Vanguard is actively exploring additional commercial applications for the innovative system. “Oil Guard completely alters the way our customers look at oil changes. But, at its core, this new system is about increasing productivity — the same driving force behind all Vanguard innovations,” said Rick Zeckmeister, vice president of marketing and planning at Briggs & Stratton. “Vanguard’s ability to work with its sister company, Ferris, provided unique development insights from the perspective of an equipment manufacturer and helped us engineer a better overall solution. This oil management system shows strong potential for commercial applications outside of turf.” The Vanguard Oil Guard System works by continuously exchanging oil between the engine and a 5-quart external oil reservoir. Its design protects oil from thermal breakdown, which extends oil maintenance intervals and produces a cooler-running engine. Direct access to the oil filter and drain tube results in quicker, easier and mess-free oil changes. Contractors operating commercial equipment with a Vanguard engine featuring the Oil Guard System will extend their recommended oil change intervals from 100 to 500 hours. This decreases the time and costs associated with conducting oil changes. The Vanguard Oil Guard System is a factory-integrated technology, not an aftermarket add-on, so Vanguard’s 3-year commercial engine limited warranty applies. 08P5 Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Torque: 3ft-lbs or 4.1Nm* Displacement (cc): 125 Cylinder: Aluminium Bore & Stroke (mm): 60.4 x 44.45 Fuel tank capacity (l): 0.75 Oil capacity (l): 0.44 Dry weight (kg): 8.2 Dimensions LxWxH (mm): 347 x 305 x 242 Features: Mechanical governor Limited Warranty†: 2 Year Domestic. 90 Day Commercial 08P5 Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Torque: 4.5ft-lbs or 6.1Nm* Displacement (cc): 125 Cylinder: Aluminium Bore & Stroke (mm): 60.4 x 44.45 Fuel tank capacity (l): 0.75 Oil capacity (l): 0.44 Dry weight (kg): 8.2 Dimensions LxWxH (mm): 347 x 305 x 242 Features: Mechanical governor Limited Warranty†: 2 Year Domestic, 90 Day Commercial 09P6 Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Torque: 5ft-lbs or 6.8Nm* Displacement (cc): 140 Cylinder: Aluminium Bore & Stroke (mm): 63.4 x 44.45 Fuel tank capacity (l): 0.8 Oil capacity (l): 0.44 Dry weight (kg): 8.2 Dimensions LxWxH (mm): 347 x 305 x 242 Features: Mechanical governor, RapidStartTM Limited Warranty†: 2 Year Domestic 09P7 Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Torque: 5.5ft-lbs or 7.5Nm* Displacement (cc): 140 Cylinder: Aluminium Bore & Stroke (mm): 63.4 x 44.45 Fuel tank capacity (l): 0.8 Oil capacity (l): 0.44 Dry weight (kg): 8.2 Dimensions LxWxH (mm): 347 x 305 x 242 Features: Mechanical governor, ReadyStart®, Paper air-filter Limited Warranty†: 2 Year Domestic, 90 Day Commercial 093J Engine type: Single cylinder, OHV (Overhead Valve), 4-stroke, air-cooled Gross Torque: 6.25ft-lbs or 8.5Nm* Displacement (cc): 150 Cylinder: Aluminium Bore & Stroke (mm): 65.6 x 44.45 Fuel tank capacity (l): 1.0 Oil capacity (l): 0.44 Dry weight (kg): 8.2 Dimensions LxWxH (mm): 351 x 308 x 249 Features: Mechanical Governor, ReadyStart® Limited Warranty†: 2 Year Domestic, 90 Day Commercial 103M Engine type: Single cylinder, OHV (Overhead Valve), 4-stroke, air-cooled Gross Torque: 6.75ft/lb or 9.2Nm* Displacement (cc): 163 Cylinder: Aluminium Bore & Stroke (mm): 68.3 x 44.5 Fuel tank capacity (l): 1.0 Oil capacity (l): 0.44 Dry weight (kg): 8.5 Dimensions LxWxH (mm): 335 x 213 x 256 Features: ReadyStart®, MechanicalGovernor, Super Lo-Tone™ Muffler, Large Angle Fuel Fill, Just Check & Add™ Oil, Paper Air Filter Limited Warranty†: 2 Year Domestic 104M Engine type: Single cylinder, OHV (Overhead Valve), 4-stroke, air-cooled Gross Torque: 7.25ft/lb or 9.8Nm* Displacement (cc): 163 Cylinder: Aluminium Bore & Stroke (mm): 68.3 x 44.5 Fuel tank capacity (l): 1.0 Oil capacity (l): 0.44 Dry weight (kg): 8.5 Dimensions LxWxH (mm): 335 x 213 x 256 Features: ReadyStart®, Mechanical Governor, Super Lo-Tone™ Muffler, Large Angle Fuel Fill, Just Check & Add™ Oil, Paper Air Filter Limited Warranty†: 2 Year Domestic 104M Engine type: Single cylinder, OHV (Overhead Valve), 4-stroke, air-cooled Gross Torque: 7.25ft/lb or 9.8Nm* Displacement (cc): 163 Cylinder: Aluminium Bore & Stroke (mm): 68.3 x 44.5 Fuel tank capacity (l): 1.0 Oil capacity (l): 0.44 Dry weight (kg): 8.5 Dimensions LxWxH (mm): 335 x 213 x 256 Features: ReadyStart®, Mechanical Governor, Super Lo-Tone™ Muffler, Large Angle Fuel Fill, Just Check & Add™ Oil, Paper Air Filter, Instart “Instant starting Technology”. Limited Warranty†: 2 Year Domestic, 90 Day Commercial 1008 Engine type: Single cylinder, 4-stroke, air-cooled, DOV® (Direct Overhead Valve) Gross Torque: 7.5ft-lbs or 10.2Nm* Displacement (cc): 161 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 64.0 x 50.0 Fuel tank capacity (l): 1.0 Oil capacity (l): 0.6 Dry weight (kg): 12.7 Dimensions LxWxH (mm): 369 x 325 x 254 Features: ReadyStart® Optional: ElectricStart® Limited Warranty†: 2 Year Domestic, 1 Year Commercial 122Q3 Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Torque: 8.5ft-lbs or 11.5Nm* Displacement (cc): 190 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 68.3 x 51.8 Fuel tank capacity (l): 1.1 Oil capacity (l): 0.7 Dry weight (kg): 13 Dimensions LxWxH (mm): 397 x 326 x 238 Features: ReadyStart®, Dual element air cleaners Optional: ElectricStart®, Oil Filter Limited Warranty†: 2 Year Domestic, 2 Year Commercial 122S Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Torque: 8.75ft-lbs or 11.9Nm* Displacement (cc): 190 Cylinder: Aluminium Bore & Stroke (mm): 68.3 x 51.8 Fuel tank capacity (l): 1.1 Oil capacity (l): 0.7 Dry weight (kg): 13 Dimensions LxWxH (mm): 397 x 326 x 238 Features: ReadyStart® Optional: ElectricStart®, Oil Filter Limited Warranty†: 2 Year Domestic, 90 Day Commercial 14D9 Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Torque: 10ft-lbs or 13.6Nm* Displacement (cc): 223 Cylinder: Aluminium Bore & Stroke (mm): 74.0 x 51.3 Fuel tank capacity (l): 1.1 Oil capacity (l): 0.7 Dry weight (kg): 14.1 Dimensions LxWxH (mm): 401 x 339 x 257 Features: Super Lo-Tone™ Muffler, ReadyStart®, Paper air-filter Limited Warranty†: 2 Year Domestic, 90 Day Commercial 100802 Engine type: Single cylinder, DOV® (Direct Overhead Valve), 4-stroke, air-cooled Gross Torque: 7.5ft-lbs or 9.5Nm* Displacement (cc): 161 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 64.0 x 50.0 Fuel tank capacity (l): 1.0 Oil capacity (l): 0.6 Dry weight (kg): 12.7 Dimensions LxWxH (mm): 369 x 325 x 254 Features: ReadyStart® Limited Warranty†: 3 Year Commercial 21R7 Engine type: Single cylinder, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 10.5* Displacement (cc): 344 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 87.3 x 57.5 Fuel tank capacity (l): 2.6 (optional) Oil capacity (l): 1.4 Dry weight (kg): 26.8 Dimensions LxWxH (mm): 452 x 393 x 327 Features: AVS® Optional: Oil Filter, Rewind Start, Fuel Tank Limited Warranty†: 2 Year Domestic, 90 Days Commercial 21R8 Engine type: Single cylinder, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 11.5* Displacement (cc): 344 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 87.3 x 57.5 Fuel tank capacity (l): 2.6 (optional) Oil capacity (l): 1.4 Dry weight (kg): 26.8 Dimensions LxWxH (mm): 452 x 393 x 327 Features: AVS® Optional: Oil Filter, Rewind Start, Fuel Tank Limited Warranty†: 2 Year Domestic, 90 Days Commercial 31S7 Engine type: Single cylinder,4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 15.5* Displacement (cc): 500 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 90.5 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 411 x 327 Features: AVS®, Oil Filter, Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 31S8 Engine type: Single cylinder,4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 16.5* Displacement (cc): 500 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 90.5 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 411 x 327 Features: AVS®, Oil Filter, Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 31S9 Engine type: Single cylinder,4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 17.5* Displacement (cc): 500 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 90.5 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 411 x 327 Features: AVS®, Oil Filter, Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 33R7 Engine type: Single cylinder, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 18.5* Displacement (cc): 540 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 94.0 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 411 x 327 Features: AVS®, Oil Filter, Full Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 33R8 Engine type: Single cylinder, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 19* Displacement (cc): 540 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 94.0 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 411 x 327 Features: AVS®, Oil Filter, Full Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 31R5 Engine type: Single cylinder,4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 13.5* Displacement (cc): 500 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 90.5 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 393 x 327 Features: AVS®, Oil Filter, Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 31R6 Engine type: Single cylinder,4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 14.5* Displacement (cc): 500 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 90.5 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 393 x 327 Features: AVS®, Oil Filter, Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 31R7 Engine type: Single cylinder,4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 15.5* Displacement (cc): 500 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 90.5 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 393 x 327 Features: AVS®, Oil Filter, Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 31R8 Engine type: Single cylinder,4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 16.5* Displacement (cc): 500 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 90.5 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 393 x 327 Features: AVS®, Oil Filter, Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 31R9 Engine type: Single cylinder,4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 17.5* Displacement (cc): 500 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 90.5 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 393 x 327 Features: AVS®, Oil Filter, Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 33S7 Engine type: Single cylinder, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 18.5* Displacement (cc): 540 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 94.0 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 411 x 327 Features: AVS®, Oil Filter, Full Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 33S8 Engine type: Single cylinder, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 19* Displacement (cc): 540 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 94.0 x 77.8 Fuel tank capacity (l): – Oil capacity (l): 1.4 Dry weight (kg): 29.5 Dimensions LxWxH (mm): 479 x 411 x 327 Features: AVS®, Oil Filter, Full Pressure Lubrication Limited Warranty†: 2 Year Domestic, 1 Year Commercial 40R6 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 16* Displacement (cc): 656cc Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 40N7 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 18* Displacement (cc): 656cc Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 40N8 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 20* Displacement (cc): 656cc Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 40U7 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 18* Displacement (cc): 656 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 40U8 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 20* Displacement (cc): 656 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 40T6 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 16* Displacement (cc): 656 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 40T7 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 18* Displacement (cc): 656 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 40T8 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 20* Displacement (cc): 656 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 44N6 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 22* Displacement (cc): 724 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 44N7 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 23* Displacement (cc): 724 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 44N8 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 24* Displacement (cc): 724 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 44T6 Engine type: V-Twin, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 22* Displacement (cc): 724 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 490 x 462 x 399 Features: Oil Filter, Pressure Lubrication, Cyclonic a/c Optional: Integrated Cyclonic Air Filter, Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 44T7 Engine type: V-Twin, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 23* Displacement (cc): 724 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 490 x 462 x 399 Features: Oil Filter, Pressure Lubrication, Cyclonic a/c Optional: Integrated Cyclonic Air Filter, Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 44T8 Engine type: V-Twin, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 24* Displacement (cc): 724 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 490 x 462 x 399 Features: Oil Filter, Pressure Lubrication, Cyclonic a/c Optional: Integrated Cyclonic Air Filter, Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 44T9 Engine type: V-Twin, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 25* Displacement (cc): 724 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 490 x 462 x 399 Features: Oil Filter, Pressure Lubrication, Cyclonic a/c Optional: Integrated Cyclonic Air Filter, Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 44U6 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 22* Displacement (cc): 724 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 44U7 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 23* Displacement (cc): 724 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 44U8 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 24* Displacement (cc): 724 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 79.2 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 479 x 393 x 327 Features: Oil Filter, Pressure Lubrication Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 49S7 Engine type: V-Twin, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 26* Displacement (cc): 810 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 73.8 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 490 x 462 x 399 Features: Oil Filter, Pressure Lubrication, Cartridge with Prefilter Optional: Integrated Cartridge with Prefilter, Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 49S8 Engine type: V-Twin, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 27* Displacement (cc): 810 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 73.8 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 490 x 462 x 399 Features: Oil Filter, Pressure Lubrication, Cartridge with Prefilter Optional: Integrated Cartridge with Prefilter, Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 49T7 Engine type: V-Twin, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 26* Displacement (cc): 810 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 73.8 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 490 x 462 x 399 Features: Oil Filter, Pressure Lubrication, Integrated Cyclonic Air Filter Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 49T8 Engine type: V-Twin, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 27* Displacement (cc): 810 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 73.8 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 1.9 Dry weight (kg): 37.6 Dimensions LxWxH (mm): 490 x 462 x 399 Features: Oil Filter, Pressure Lubrication, Integrated Cyclonic Air Filter Optional: Electronic Fuel Management Limited Warranty†: 2 Year Domestic, 1 Year Commercial 0831 Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 3.5* Displacement (cc): 127 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 62.0 x 42.0 Fuel tank capacity (l): 1.8 Oil capacity (l): 0.6 Dry weight (kg): 13.0 Dimensions LxWxH (mm): 261 x 347 x 326 Limited Warranty†: 2 Year Domestic, 1 Year Commercial 1062 Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 5* Displacement (cc): 163 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 68.0 x 45.0 Torque (Nm) @ 3600 rpm: 7.0 Fuel tank capacity (l): 3.3 Oil capacity (l): 0.61 Dry weight (kg): 13.0 Dimensions LxWxH (mm): 364 x 385 x 325 Limited Warranty†: 2 Year Domestic, 1 Year Commercial 130G Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 6.5* Displacement (cc): 208 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 68.3 x 55.9 Fuel tank capacity (l): 3.8 Oil capacity (l): 0.6 Dry weight (kg): 15.5 Dimensions LxWxH (mm): 409 x 270 x 356 Limited Warranty†: 2 Year Domestic, 1 Year Commercial 25T2 Engine type: Single cylinder, 4-stroke, air-cooled, OHV (Overhead Valve) Gross Horsepower: 13.5* Displacement (cc): 420 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 90.0 x 66.0 Torque (Nm) @ 3600 rpm: 21.0* Fuel tank capacity (l): 6.6 Oil capacity (l): 1.1 Dry weight (kg): 31.0 Dimensions LxWxH (mm): 405 x 450 x 457 Limited Warranty†: 2 Year Domestic, 1 Year Commercial 100802 Engine type: Single cylinder, DOV® (Direct Overhead Valve), 4-stroke, air-cooled Gross Torque: 7.5ft-lbs or 9.5Nm* Displacement (cc): 161 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 64.0 x 50.0 Fuel tank capacity (l): 1.0 Oil capacity (l): 0.6 Dry weight (kg): 12.7 Dimensions LxWxH (mm): 369 x 325 x 254 Features: ReadyStart® Limited Warranty†: 3 Year Commercial 3057 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 16* Displacement (cc): 479 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 68.0 x 66.0 Fuel tank capacity (l): – Oil capacity (l): 1.7 Dry weight (kg): 32.4 Dimensions LxWxH (mm): 279 x 410 x 438 Features: Full Pressure Lubrication, Oil Filter Optional: Rewind Start Limited Warranty†: 3 Year Commercial 3567 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 18* Displacement (cc): 570 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 72.0 x 70.0 Fuel tank capacity (l): – Oil capacity (l): 1.7 Dry weight (kg): 33.3 Dimensions LxWxH (mm): 318 x 407 x 449 Features: Full Pressure Lubrication, Oil Filter Limited Warranty†: 3 Year Commercial 3857 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 21* Displacement (cc): 627 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 75.5 x 70.0 Fuel tank capacity (l): – Oil capacity (l): 1.7 Dry weight (kg): 35 Dimensions LxWxH (mm): 318 x 407 x 449 Features: Full Pressure Lubrication, Oil Filter Limited Warranty†: 3 Year Commercial 3867 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 23* Displacement (cc): 627 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 75.5 x 70.0 Fuel tank capacity (l): – Oil capacity (l): 1.7 Dry weight (kg): 35 Dimensions LxWxH (mm): 318 x 407 x 449 Features: Full Pressure Lubrication, Oil Filter Limited Warranty†: 3 Year Commercial 49V6 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 24* Displacement (cc): 810 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 84.0 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 2.0 Dry weight (kg): 41.3 Dimensions LxWxH (mm): 506.4 x 470.6 x 581.4 Features: Full Pressure Lubrication, Oil Filter Limited Warranty†: 3 Year Commercial 49R9 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 26* Displacement (cc): 810 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 84.0 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 2.0 Dry weight (kg): 41.3 Dimensions LxWxH (mm): 506.4 x 470.6 x 581.4 Features: Full Pressure Lubrication, Oil Filter Limited Warranty†: 3 Year Commercial 49E5 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 24* Displacement (cc): 810 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 84.0 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 2.0 Dry weight (kg): 41.3 Dimensions LxWxH (mm): 506.4 x 470.6 x 581.4 Features: Full Pressure Lubrication, Oil Filter EFI, Donaldson Cyclonic a/c Limited Warranty†: 3 Year Commercial 49E8 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 28* Displacement (cc): 810 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 84.0 x 73.4 Fuel tank capacity (l): – Oil capacity (l): 2.0 Dry weight (kg): 41.3 Dimensions LxWxH (mm): 506.4 x 470.6 x 581.4 Features: Full Pressure Lubrication, Oil Filter EFI, Donaldson Cyclonic a/c Limited Warranty†: 3 Year Commercial 5417 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 28* Displacement (cc): 896 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 86.0 x 78.0 Fuel tank capacity (l): – Oil capacity (l): 2.3 Dry weight (kg): 56.7 Dimensions LxWxH (mm): 601 x 514 x 626 Features: Full Pressure Lubrication, Oil Filter, Cyclonic Air Cleaner Optional: Exhaust Limited Warranty†: 3 Year Commercial 5427 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 30* Displacement (cc): 896 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 86.0 x 78.0 Fuel tank capacity (l): – Oil capacity (l): 2.3 Dry weight (kg): 56.7 Dimensions LxWxH (mm): 601 x 514 x 626 Features: Full Pressure Lubrication, Oil Filter, Cyclonic Air Cleaner Optional: Exhaust Limited Warranty†: 3 Year Commercial 5437 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 32* Displacement (cc): 896 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 86.0 x 78.0 Fuel tank capacity (l): – Oil capacity (l): 2.3 Dry weight (kg): 56.7 Dimensions LxWxH (mm): 601 x 514 x 626 Features: Full Pressure Lubrication, Oil Filter, Cyclonic Air Cleaner Optional: Exhaust Limited Warranty†: 3 Year Commercial 54E6 Engine type: V-Twin, 4-stroke, air cooled, OHV (Overhead Valve) Gross Horsepower: 33* Displacement (cc): 896 Cylinder: Cast Iron Sleeve Bore & Stroke (mm): 86.0 x 87.0 Fuel tank capacity (l): – Oil capacity (l): 2.3 Dry weight (kg): 56.7 Dim